

### **B** Features

- Single pulse energy up to 2 J
- Easy switch for dual wavelengths 1064&532 nm
- Patent design with compacy size
- Beam homogenization technology with flat-top beam profile
- Hardened design to ensure long term stability
- CE certificate
- more than 4000 units delivery

## Applications

- Tattoo removal
- Pigmentation removal
- · Laser toning, skin whitening



# Classic nanosecond cosmetic lasers

Mianna-Q series lasers have been developed since 1997. This series were designed specifically for medical cosmetology. Due to the features as compact size, high efficiency, perfect beam profile, high quality, Mianna-Q series have been delivered around 4000 units all over the world.

Mianna-Q series lasers apply unique one lamp two rods patent design. This technology not only provides compact size and high conversion efficiency, but also saves the system integrator's cost for power supply and cooling system. Besides, Mianna-Q lasers apply advanced beam homogenization technology. The beam distribution is perfectly flat-top which generates better curative effects.







## **Specifications**

| Models             |                 | MQ/E        | MQ                    | MQ/X        |
|--------------------|-----------------|-------------|-----------------------|-------------|
| Repetition Rate    | Sigle pulse     | 1-10Hz      | 1-10Hz                | 1-5Hz       |
|                    | Double pulse    | 1-5Hz       | 1-5Hz                 |             |
|                    | Long pulse      | 1-5Hz       | 1-5Hz                 |             |
| Pulse Energy       | Sigle pulse     | 800mJ@1064  | 1200mJ@1064           | 2000mJ@1064 |
|                    |                 | 320 mJ@532  | 480 mJ@532            | 600 mJ@532  |
|                    | Double pulse    | 1200mJ@1064 | 2000mJ@1064           |             |
|                    |                 | 480 mJ@532  | 900 mJ@532            |             |
|                    | Long pulse      | 1000mJ@1064 | 2000mJ@1064           | 2000mJ@1064 |
| Energy Stability   | 1064nm          | ≤1%         | ≤1%                   | ≤2%         |
|                    | 532nm           | ≤2%         | ≤2%                   | ≤3%         |
| Pulse Width(ns)    | Q mode          |             | 8ns@1064nm, 7ns@532nm |             |
|                    | Long pulse mode |             | 200μs                 |             |
| Beam Diameter      |                 | 8mm         | 8mm                   | 12mm        |
| Cooling            |                 |             | Air to water          |             |
| Electrical Service |                 |             | 220V-50/60Hz-10A      |             |
| Power Consumption  |                 | 750W        | 750W                  | 1000W       |

## **Dimensions**



